

Cutting Head Part Numbers

Cutting Head Part Numbers

	Head/Blade Type	Part Number	Trimmer Line Diameters		FSE 60*	FSA 65*	FSA 85*	FSA 90 R	FS 38 FS 40 C-E FS 45* FS 46*	FS 50 C-E	FS 55 FS 56 C-E**	FS 55 R FS 56 RC-E FS 70 R, FS 94 R	FS 80	FS 80 R FS 90 R FS 110 R FS 130 R	FS 100 RX FS 110 RX	FS 90 FS 110 FS 130	FS 240 FS 250	FS 240 R FS 250 R	FS 310 FS 350	FS 360 C-E FS 460 C-EM	FS 450 K	FS 550 FS 560 C-EM	FSB-KM with KM 55 R, 90 R, 110 R	FS-KM with KM 55 R, KM 56 R	FS-KM with KM 90 R, 94 R, 110 R, 130 R		
			Standard	Optional																							
STIHL SuperCut™ head: Fully automatic, double nylon line is auto- matically kept at the proper cutting length.	STIHL SuperCut™	20-2	4002 710 2184	.095"	—																						
	STIHL SuperCut™	40-2	4003 710 2142	.095"	—																						
AutoCut® head: Double line for trimming and mowing. Nylon line is fed automatically by TapAction™. AutoCut® C 5-2 EasySpool™ version available.	AutoCut® C	4-2	4006 710 2123	.080"	—																						
	AutoCut®	5-2	4006 710 2103	.080"	—																						
	AutoCut® C	5-2	4006 710 2106	.080"	—																						
	AutoCut® C	25-2	4002 710 2196	.095"	—																						
	AutoCut®	11-2	4004 710 2192	.095"	.080"																						
	AutoCut®	25-2	4002 710 2191	.095"	.105"																						
	AutoCut®	30-2	4002 710 2187	.105"	.118"																						
	NEW! AutoCut®	36-2	4002 710 2170	.105"	.118"/.130"																						
	AutoCut®	40-2	4003 710 2189	.105"	.118"																						
	NEW! AutoCut®	46-2	4003 710 2115	.105"	.118"/.130"																						
	AutoCut®	40-4	4005 710 2102	.105"	.118"																						
NEW! AutoCut®	56-2	4005 710 2107	.105"	.118"/.130"																							
DuroCut head: Ideal trimmer head if you prefer manual heads that require precut lengths of nylon line, even when operating in severe applications.	DuroCut	5-2	4006 710 2125	.080"	.065"/.095"																						
	DuroCut	20-2	4002 710 2167	.120"	.080/.095/.105"																						
	DuroCut	40-4	4005 710 2106	.155"	.120/.130"																						
FixCut™ head: Lightweight and quick loading. Insert 8" piece of trimmer line in each eyelet. <i>Discontinued in 2014 (Available while supplies last)</i>	FixCut™	5-2	4006 710 2118	.095"	.080"																						
	FixCut™	25-2	4002 710 2158	.095"	.080/.120/.130"																						
	FixCut™	30-2	4001 710 2103	—	.080/.095/.105"																						
TrimCut™ head: Manual-feed nylon head is particularly suitable for mowing low-growing grass around solid obstacles.	TrimCut™	31-2	4002 710 2156	.105"	.095"																						
	TrimCut™	41-2	4003 710 2108	.105"	.095"																						
	TrimCut™	51-2	4005 710 2104	.105"	.095"																						
STIHL PolyCut™ head: A universal cutting tool for trimming large areas. Fitted with three thermoplastic blades.	STIHL PolyCut™	5-3	4004 710 2180																								
	STIHL PolyCut™	6-3	4006 710 2104																								
	STIHL PolyCut™	20-3	4002 710 2189																								
	STIHL PolyCut™	41-3	4003 710 2114																								
Metal blade: Steel with 4 cutting edges to work on large areas of tough weeds and heavy grass.	Grass - 4	25.4 mm	4001 713 3801																								
	Grass - 4	20 mm	4000 713 3801																								
Metal blade: Steel with 8 teeth to cut thick, dry weeds and reeds.	Grass - 8	25.4 mm	4001 713 3803																								
	Grass - 8	20 mm	4000 713 3802																								
Brush knife: Steel, for thinning and clearing tough, tangled weeds, undergrowth and scrub.	Brush Knife - 250 mm	25.4 mm	4112 713 4100																								
	Brush Knife - 300 mm	20 mm	4119 713 4100																								
	Brush Knife - 350 mm	20 mm	4110 713 4100																								
Circular saw blade, scratcher tooth: Steel, for gnarled bushes and thin tree trunks.	Scratcher - 200 mm	25.4 mm	4112 713 4201																								
	Scratcher - 200 mm	20 mm	4000 713 4200																								
	Scratcher - 225 mm	20 mm	4000 713 4205																								
	Scratcher - 250 mm	20 mm	4104 713 4200																								
Circular saw blade, chisel tooth: Steel, for gnarled bushes and thin tree trunks (depends on diameter of trunk and techniques used).	Chisel - 200 mm	25.4 mm	4112 713 4203																								
	Chisel - 200 mm	20 mm	4119 713 4200																								
	Chisel - 225 mm	20 mm	4110 713 4204																								

* Trimmers equipped with loop handles. For models that are/were available with optional handles, "R" denotes loop handle version.

Note: Numbers with "mm" show arbor size.

Consult your instruction manual or your authorized STIHL Dealer for approved cutting head/deflector combinations.

● Approved for use with designated unit as originally equipped.

** When using Grass-4 and Grass-8 metal cutting blades with FS 56 C-E, trimmer must be equipped with deflector. A deflector is always necessary. See dealer for more details.

■ Approved for use with loop handle (R) only if equipped with barrier bar deflector kit and a single or double shoulder harness.

◆ Approved for use with bike handle, double harness and limit stop.

*** Not for use on FS 560 C-EM

1 Not for use on FS 240 or FS 240 R

2 Not for use on FS 94 R

NOTE: Barrier bar and large deflector must be attached when using a metal blade with loop (R) handle trimmer.

IMPORTANT INFORMATION

WARNING: Improper use of any brushcutter trimmer can cause serious or fatal injury. Read, understand and follow all safety instructions in your instruction manual. To reduce the risk of injury from blade contact, circular saw blades may be used on FS brushcutters that have a bicycle handle and double shoulder harness and not on FS brushcutters with a "J" handle or loop handle (R). Other rigid blades may be used on FS brushcutters having a bicycle handle, a "J" handle, or a loop handle equipped with a barrier bar. To reduce the risk of eye injury, always wear proper eye protection. Always use the appropriate deflector for the type of cutting attachment, as explained in your instruction manual.