

Café™ Energy Star® 27.8 Cu. Ft. French-Door Refrigerator with Keurig® K-Cup® Brewing System

CFE28UP3MD1

CAFÉ



Matte Black
with Brushed
Stainless handles



FEATURES & BENEFITS

Brew your favorite morning latte or cappuccino from a **Keurig K-Cup brewing system** built directly into the refrigerator.

Steep a relaxing herbal tea or prepare light & fluffy couscous with an adjustable **hot water dispenser** that provides precise temperatures and measurements.

Use your voice or **smart device** to preheat water from your refrigerator while you relax in another part of the house.

Leave the measuring cups in the drawer with a **Precise Fill setting** that dispenses an exact amount of water with just a touch.

Keep key ingredients fresh and within sight with a full-width, electronic, **temperature-controlled drawer** that uses an LED colored lighting system.

Food remains fresh longer with **TwinChill™ evaporators** that accurately maintain and control separate freezer and refrigerator environments.

Display groceries like a gallery with **showcase LED lighting** positioned throughout the interior to spotlight your favorite foods and containers.

Easily fill tall glasses and pitchers using a **stainless steel dispenser** with pullout tray that is designed to hold larger containers.

Add extra space right inside the door with a **drop-down tray** that makes storage simple.

Display pictures on the fridge in a whole new way with a built-in a **color LCD screen with photo upload**.

APPEARANCE

Exterior design	Flat doors
Handle design	GE Café
Hidden door hinge(s)	Yes
Textured steel case	Case only—Dark gray

FEATURES

Configuration	French door
WiFi connect	Built-in
Connected capabilities	Amazon Alexa; The Google Assistant; IFTTT
Temperature management features	Turbo Cool setting
Temperature management system	TwinChill™ evaporators
Defrost type	Frost Guard
Control type	External touch color LCD
Dispenser	Large stainless steel; cubes, crushed ice and water
Dispenser features	Hot water; Precise Fill; LCD screen controls; USB port for photo upload; Door alarm; LED dispenser light; Water filter indicator light; Single serve K-cup
Icemaker	Space saving ice
Water filtration	Advanced filtration system (RPWFE); Removes pharmaceuticals; Water filter indicator light
Filter location	Left wall
Fresh food cabinet drawers	3 total; 2 adjustable humidity drawers; 1 full-width, adjustable temperature; Electronic temperature control w/colored LED lighting
Fresh food cabinet shelves	5 total—glass with silver trim; 4 split adjustable; 1 full-width; 3 spill proof; 1 Quick Space shelf
Fresh food door bins	6 total (4 stainless steel design); 2 adjustable; 3 with gallon storage
Fresh food door features	Dairy compartment; Drop down tray
Fresh food features	Showcase LED lighting (7); Deli pan
Freezer door bins	1 tilt-out
Freezer storage baskets	2 full-width
Freezer features	Turbo Freeze; interior lighting—showcase LED (2)
Exterior style	Free-standing
Leveling system	2 front leveling legs
Performance features	Easily removable door gaskets; Sabbath Mode capable

CAPACITY

Total capacity (cubic feet)	27.8 cu. ft.
Fresh food capacity	18.6 cu. ft.
Freezer capacity	9.2 cu. ft.

WEIGHTS & DIMENSIONS

Overall depth	36-1/4 in.
Overall height	69-7/8 in.
Overall width	35-3/4 in.
Case depth without door	29-3/8 in.
Depth with door open 90°	48-3/8 in.
Depth without handle	35-1/4 in.
Height to top of case	69 in.
Width with door open 90° including handle	44-3/4 in.
Approximate shipping weight	423 lb.
Net weight	388 lb.

Café™ Energy Star® 27.8 Cu. Ft. French-Door Refrigerator with Keurig® K-Cup® Brewing System




CFE28UP3MD1

WARRANTY

Parts warranty	Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
Labor warranty	Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
Warranty notes	See written warranty for full details

DIMENSIONS



Height to top of door (in.) A	70-1/2
Height to top of hinge (in.) B	69-7/8
Height to top of case (in.) C	69
Case depth without door (in.) D**	29-3/8
Case depth less door handle (in.) E**	35-1/4*
Case depth with door handle (in.) F**	36-1/4
Depth with fresh food door open 90° (in.) G**	48-3/8
Width (in.) H	35-3/4
Width with door open 90° with door handle (in.) I	44-3/4
Width with doors open fully (in.) J	67-1/4
Min distance between side of case and wall, in either direction, to allow doors to open fully (in.) K	16-3/8
Depth with FZ door completely open (w/o handle) (in.) X	51-7/8
Depth with FZ door completely open (w/ handle) (in.) Y	53-3/8

*Includes hot water knob.
 **Water hookup fits in back air clearance when calculating installation depth.

ADDITIONAL ACCESSORIES



CXLB3H3PMBZ
 Brushed Bronze
 3 handles
 (Standard on Matte White)



CXLB3H3PMSS
 Brushed Stainless
 3 handles
 (Standard on Matte Black)



CXLB3H3PMBT
 Brushed Black
 3 handles



CXLB3H3PMCU
 Brushed Copper
 3 handles

For answers to your Café™ product questions, visit our website at cafeappliances.com.